Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-086-1192

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.234 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.469 inches |
| Minimum Inside Bending Radius: |
| 3.250 inches |
| Exterior Color: |
| Natural |
| End Application: |
| Grumman aerospace a-10 aircraft |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 16000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 4000.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 8000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| |

9.000 inches



Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0