NSN 4720-01-086-5048

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-086-5048

Cross Sectional Shape:						
Round						
Thread Class:						
3b 2nd end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.344 inches						
Tempurature Rating:						
-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response						
Outside Diameter:						
0.547 inches						
Minimum Inside Bending Radius:						
2.500 inches						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 2nd end						
Burst Test Pressure:						
1000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire						
Maximum Operating Pressure:						
250.0 pounds per square inch						
Thread Size:						
0.562 inches 2nd end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
500.0 pounds per square inch						
Flow Angle:						
45.0 degrees 2nd end						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
8.000 inches						
Thread Series Designator:						
Unf 2nd end						
Shelf Life:						

NSN 4720-01-086-5048

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0