Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-087-7088

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.235 inches |
| Tempurature Rating: |
| -450.0 degrees fahrenheit single response and 1200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.439 inches |
| Minimum Inside Bending Radius: |
| 2.500 inches |
| Inner Conveying Tube Style: |
| Annular open-pitch corrugated |
| End Application: |
| Grumman aircraft, model a10 |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Identical ends |
| Thready Qty Per Inch (tpi): |
| 20 1st end |
| Burst Test Pressure: |
| 9800.0 pounds per square inch |
| Maximum Operating Pressure: |
| 1625.0 pounds per square inch |
| Thread Size: |
| 0.437 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Measuring Method And Length: |
| 8.750 inches excluding end fittings |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Uns 1st end |
| |

NSN 4720-01-087-7088

Metallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

