Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-087-8174

Cross Section	nal Shape:
Round	
Thread Class	:
3b 1st end	
Thread Direct	tion:
Right-hand 1st	t end
Inside Diamet	ter:
0.500 inches	
Tempurature	Rating:
-65.0 degrees	fahrenheit and 400.0 degrees fahrenheit single response
Outside Diam	eter:
0.750 inches	
Minimum Insi	de Bending Radius:
1.000 inches	
Angle Betwee	en Rigid Elbow Fittings In Deg:
76.0	
Connection S	ityle:
Swivel nut flare	e 1st end
End Connecti	ion Design:
Elbow 2nd end	t de la constante de
Connection T	уре:
Threaded inter	rnal tube 1st end
Burst Test Pro	essure:
750.0 pounds	per square inch
Layer Compo	sition And Location:
1st layer spiral	lly wrapped polytetrafluoroethylene impregnated glass fiber and outer layer braided corrosion resistant steel wire
Maximum Op	erating Pressure:
200.0 pounds	per square inch
Thread Size:	
0.750 inches 1	st end
Seat Angle:	
37.0 degrees 1	1st end
Hydrostatic T	est Pressure:
400.0 pounds	per square inch
Flow Angle:	
90.0 degrees 1	1st end
Inside Surfac	e Condition:
Convoluted	
Measuring Me	ethod And Length:
15.500 inches	working
Thread Series	s Designator:
Unjf 1st end	

NSN 4720-01-087-8174

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0