Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-087-9976

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 450.0 degrees	s fahrenheit single response
Outside Diameter:	
0.390 inches	
Minimum Inside Bending Radius:	
2.000 inches	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
10000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
12.00 millimeters 2nd end	
Seat Angle:	
37.0 degrees 2nd end	
Flow Angle:	
45.0 degrees 2nd end	
Vacuum In Torr:	
28.0	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
20.669 inches working	
Thread Series Designator:	
Iso m 2nd end	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 4720-01-087-9976

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

