## NSN 4720-01-088-1083

Nonmetallic Hose - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-088-1083 **Cross Sectional Shape:** Round **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 350.0 degrees fahrenheit single response **Outside Diameter:** 0.760 inches **End Application:** Nsn 2320-01-195-7641 hemtt (heavy expanded mobility tactical truck) **Burst Test Pressure:** 340.0 pounds per square inch single response **Layer Composition And Location:** 1st layer woven polyester fiber cord or 2nd layer woven polyester fiber cord or 3rd layer woven polyester fiber cord or outer layer molded rubber, synthetic **Maximum Operating Pressure:** 50.0 pounds per square inch single response **Hydrostatic Test Pressure:** 212.0 pounds per square inch single response **Outer Covering Environmental Protection:** Heat resistant and oil resistant and ozone resistant **Criticality Code Justification:** Feat **Inside Surface Condition:** Smooth **Measuring Method And Length:** 32.000 inches **Special Features:** Weapon system essential; outer cov. Envrmtl protection: ethylene glycol; cold resistant Material: Rubber silicone tube **Specification Data:** 81349-mil-h-62217 government specification **Specification Or Standard:** 1 type Shelf Life: N/a

Fiig:

No

A541z0

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 4720-01-088-1083

Nonmetallic Hose - Page 2 of 2



Mil-std (military Standard):

Mil-h-62217 spec.