

View Online at <https://aerobasegroup.com/nsn/4720-01-088-1727>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.730 inches

**Minimum Inside Bending Radius:**

5.000 inches

**Quick Disconnect Size:**

0.250 inches 1st end

**Connection Style:**

Push (internal) 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Internal quick disconnect 1st end

**Burst Test Pressure:**

28000.0 pounds per square inch

**Layer Composition And Location:**

1st layer spirally wrapped corrosion resistant steel fabric and 2nd layer spirally wrapped corrosion resistant steel fabric and 3rd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

7000.0 pounds per square inch

**Thread Size:**

0.250 inches 1st end

**Hydrostatic Test Pressure:**

15000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

27.190 inches

**Special Features:**

Includes plug coupling at both ends, p/n 13218e9860, aluminum

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Npsf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0