

View Online at <https://aerobasegroup.com/nsn/4720-01-088-1727>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.730 inches

Minimum Inside Bending Radius:

5.000 inches

Quick Disconnect Size:

0.250 inches 1st end

Connection Style:

Push (internal) 1st end

End Connection Design:

Straight 1st end

Connection Type:

Internal quick disconnect 1st end

Burst Test Pressure:

28000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally wrapped corrosion resistant steel fabric and 2nd layer spirally wrapped corrosion resistant steel fabric and 3rd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

7000.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Hydrostatic Test Pressure:

15000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

27.190 inches

Special Features:

Includes plug coupling at both ends, p/n 13218e9860, aluminum

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Npsf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0