## NSN 4720-01-088-9650

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-088-9650 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.313 inches **Tempurature Rating:** -55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.609 inches **Minimum Inside Bending Radius:** 2.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 4000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fabric and 2nd layer braided wire and outer layer rubber impregnated fabric **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2000.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 42.000 inches

**Thread Series Designator:** 

Unf 1st end

## NSN 4720-01-088-9650

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0