NSN 4720-01-089-2016

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-089-2016 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.000 inches **Outside Diameter:** 1.562 inches **Minimum Inside Bending Radius:** 11.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 8000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 2000.0 pounds per square inch **Thread Size:** 1.312 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Outer Covering Environmental Protection:** Mildew resistant and ozone resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 14.000 inches **Thread Series Designator:** Un 2nd end Shelf Life: N/a

Unit Of Measure:

NSN 4720-01-089-2016

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0