## NSN 4720-01-089-9890

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-089-9890

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
Quick Disconnect Size:
0.313 inches 2nd end
Connection Style:
Swivel nut with compression sleeve 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
Seat Angle: 37.0 degrees 1st end
37.0 degrees 1st end
37.0 degrees 1st end  Hydrostatic Test Pressure:
37.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch
37.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Outer Covering Environmental Protection:
37.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant
37.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant  Inside Surface Condition:
37.0 degrees 1st end  Hydrostatic Test Pressure: 3000.0 pounds per square inch  Outer Covering Environmental Protection:  Corrosion resistant  Inside Surface Condition:  Smooth

## NSN 4720-01-089-9890

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0