NSN 4720-01-090-5650

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-090-5650

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.311 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
0.450 inches
Minimum Inside Bending Radius:
1.500 inches
Exterior Color:
Natural
Quick Disconnect Size:
0.562 inches 2nd end
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
480.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
120.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
240.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

20.250 inches and 20.750 inches

NSN 4720-01-090-5650

Nonmetallic Hose Assembly - Page 2 of 2



Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources, 00624, 81755, have indicated their part numbers contained asbestos. They continue to manufacture the same part number without asbestos material

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0