

View Online at <https://aerobasegroup.com/nsn/4720-01-090-9687>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

158.0 degrees fahrenheit single response

**Outside Diameter:**

0.720 inches

**Unable To Decode:**

Unable to decode or unable to decode

**Hose Or Tubing Specification/std Data:**

Zz-h-601, grade 1, class 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

Ww-c-624, type a, style 1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting copper alloy all ends

**Connection Type:**

Threaded internal pipe 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

600.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber err-100

**Thread Size:**

0.500 inches 1st end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

180.000 inches

**Special Features:**

Two rubber washers included

**Media For Which Designed:**

**Thread Series Designator:**

Npsh 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0