Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-093-0394

**Cross Sectional Shape:** 

Round

Thread Class:

2b 1st end

# **Thread Direction:**

Right-hand 1st end

# Inside Diameter:

0.250 inches

#### Tempurature Rating:

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

#### Outside Diameter:

Between 0.566 inches and 0.718 inches

Minimum Inside Bending Radius:

4.000 inches

#### Hose Or Tubing Specification/std Data:

Mil-h-13531, type 2 or 3, class a or b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# First End Fitting Specification/std Data:

Sae j516, table 4a-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

# **Connection Style:**

Swivel nut flare 1st end

#### End Connection Design:

Straight 1st end

#### End Fitting Component And Material:

Complete fitting steel all ends

# Fitting Component And Surface Treatment:

Complete fitting cadmium and complete fitting zinc 1st end

# **Connection Type:**

Threaded internal tube 1st end

#### **Features Provided:**

Reusable end fittings

# Second End Relationship With First End:

Identical

# Burst Test Pressure:

20000.0 pounds per square inch

# First End Swivel Action Capability:

Not included

# Layer Composition And Location:

1st layer braided steel wire err-100

#### **Maximum Operating Pressure:**

5000.0 pounds per square inch

#### Unable To Decode:

Unable to decode or unable to decode

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 10000.0 pounds per square inch **Outer Covering Environmental Protection:** Mildew resistant and oil resistant and oil resistant **Inside Surface Condition:** Smooth Measuring Method And Length: 29.000 inches **Thread Series Designator:** Unf 1st end **Specification Data:** 96906-ms500083 government standard Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A542a0 Mil-std (military Standard): Mil-h-13531 spec.