

View Online at <https://aerobasegroup.com/nsn/4720-01-093-3560>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.125 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Flange Thickness:

0.234 inches 2nd end

Outside Diameter:

1.359 inches

Recess Diameter:

1.854 inches 2nd end

Recess Depth:

0.136 inches 2nd end

Minimum Inside Bending Radius:

11.000 inches

Angle Between Rigid Elbow Fittings In Deg:

130.0

Center To Center Distance Between Bolt Holes Along Width:

1.660 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.660 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.190 inches 2nd end

Flange Width:

2.190 inches 2nd end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.270 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

700.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire

Maximum Operating Pressure:

175.0 pounds per square inch

Thread Size:

1.625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

350.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Fuel resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.588 inches working and 11.010 inches working

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Hose is connected in center with a 90 degrees elbow

Supplementary Features:

This item has been reviewed for asbestos material. The current approved sources, 00624, 81205, have indicated their part numbers contained asbestos. They continue to manufacture the same part number without asbestos material

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0