Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-093-8612

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.688 inches

Tempurature Rating:

-65.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response

Outside Diameter:

1.219 inches

Minimum Inside Bending Radius:

7.750 inches

Hose Or Tubing Specification/std Data:

Mil-h-8788-12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil ms28761-12 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut with loose or integral clinch sleeve 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Socket aluminum alloy 2nd end

Fitting Component And Surface Treatment:

Nut cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided steel wire err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.062 inches 1st end

NSN 4720-01-093-8612

Nonmetallic Hose Assembly - Page 2 of 2



Seat Angle: 12.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch **Outer Covering Environmental Protection:** Cold resistant and fuel resistant and oil resistant and ozone resistant Inside Surface Condition: Smooth **Measuring Method And Length:** 90.000 inches working **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 1st end Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A542a0 Mil-std (military Standard): Mil-h-8788 spec.