

View Online at <https://aerobasegroup.com/nsn/4720-01-095-1648>

Cross Sectional Shape:

Round

Thread Class:

3b and 3a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.423 inches

Minimum Inside Bending Radius:

3.500 inches

Exterior Color:

Natural

Connection Style:

Plain 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube and external pipe 2nd end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyamide cord and 2nd layer braided polyamide cord and outer layer molded polyurethane

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.250 inches and 0.125 inches 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Hydraulic solution resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

41.000 inches

Special Features:

W/lubrication fitting on 2nd end

Thread Series Designator:

Unf and npsm 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0