

View Online at <https://aerobasegroup.com/nsn/4720-01-095-1648>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b and 3a 2nd end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.188 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.423 inches

**Minimum Inside Bending Radius:**

3.500 inches

**Exterior Color:**

Natural

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube and external pipe 2nd end

**Burst Test Pressure:**

12000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided polyamide cord and 2nd layer braided polyamide cord and outer layer molded polyurethane

**Maximum Operating Pressure:**

3000.0 pounds per square inch

**Thread Size:**

0.250 inches and 0.125 inches 2nd end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Hydraulic solution resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

41.000 inches

**Special Features:**

W/lubrication fitting on 2nd end

**Thread Series Designator:**

Unf and npsm 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0