NSN 4720-01-095-3435

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-095-3435

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.512 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.785 inches
Minimum Inside Bending Radius:
1.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
4800.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Fuel resistant
Inside Surface Condition:
Convoluted

11.250 inches working

Measuring Method And Length:

NSN 4720-01-095-3435

Nonmetallic Hose Assembly - Page 2 of 2



		•		
Ιh	read	Series	Desiar	າator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0