NSN 4720-01-095-3436

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-095-3436

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.507 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:

Smooth

NSN 4720-01-095-3436

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
7.500 inches
Thread Series Designator:
Unjf 1st end
Specification Data:
81343-as154 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0