NSN 4720-01-095-4724

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.781 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-095-4724

-40.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:
1.090 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
Maximum Operating Pressure: 1000.0 pounds per square inch
1000.0 pounds per square inch
1000.0 pounds per square inch Thread Size:
1000.0 pounds per square inch Thread Size: 1.062 inches 2nd end
1000.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle:
1000.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end
1000.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure:
1000.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 2000.0 pounds per square inch
1000.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 2000.0 pounds per square inch Flow Angle:
1000.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 2000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end
1000.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 2000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection:
1000.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 2000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant and fuel resistant
1000.0 pounds per square inch Thread Size: 1.062 inches 2nd end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 2000.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant and fuel resistant Inside Surface Condition:

NSN 4720-01-095-4724

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designate	or:
-------------------------	-----

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0