## NSN 4720-01-095-8745

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-095-8745

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.380 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
1.750 inches
Exterior Color:
Black
Connection Style:
Swivel, plain 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 2nd end
Features Provided:
Reusable end fittings
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber, synthetic and 2nd layer braided textile yarn and 3rd layer braided textile yarn and outer layer molded rubber,
synthetic
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Hydrostatic Test Pressure:
450.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
30.000 inches
Special Features:
One end fitting fixed and other end swivel; finish with electrodeposited zinc with upplementary chromate treatment

Air single response

Media For Which Designed:

## NSN 4720-01-095-8745

Nonmetallic Hose Assembly - Page 2 of 2



Thread	<b>Series</b>	Design	nator:
	0000	_00.9.	

Nptf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0