NSN 4720-01-096-0168

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-096-0168 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response **Outside Diameter:** 0.719 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal pipe 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 800.0 pounds per square inch **Layer Composition And Location:** 1st layer braided rayon cord and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.375 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 400.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and oil resistant and paint resistant **Inside Surface Condition:** Smooth

Measuring Method And Length: 300.000 inches Media For Which Designed:

Paint single response

NSN 4720-01-096-0168

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Carias	Decimates
illieau	oenes	Designator:

Nps 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0