Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-096-3183

Round         Proceed Class:         By the and         Thread Direction:         Right-hand tal end         Bytelend tal end         Dasse Direction:         Right-hand tal end         Dasse Direction:         10:40 Directer:         10:40 Directer:         12:30 inches         Minimum Inside Bending Radius:         7:380 inches         Connection Style:         Swich Int fast stand         Deroteion Type:         Swich Int fast stand         Connection Type:         Straight 1st end         Parece Provided:         Reusable end fittings         Fatures Provided:         12:10 end         Straight 1st end         Duried Direction Pesign:         12:10 end         Bust Provided:         12:00 pounds per square inch         Straight 1st end         Straight 1st end         13:12 inches 1st end         13:12 inches 1st end         14:12 inches 1st end         15:12 inches 1st end         16:12 inches 1st end         17:12 inches 1st end         17:12 inches 1st end         17:12 inches 1st end      <	Cross Sectional Shape:
B is is end         Tread Direction:         Right-hand 1st end         Inside Diameter:         0.880 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response         Outside Diameter:         1.230 inches         Minimum Inside Bending Radius:         7.380 inches         Connection Style:         Swivel nut flare 1st end         Encontion Tope:         Threade internal tube 1st end         Features Provided:         Reusable end fittings         Threade justerns:         3200.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yam and 2nd layer braided wire and outer layer rubber impregnated braided fabric         Maximum Operating Pressure:         800.0 pounds per square inch         Layer Composition And Location:         1.312 inches 1st end         Preduces 1st end         Hydrostatic Test Pressure:         1.320.0 pounds per square inch         Layer Composition And Location:         1.312 inches 1st end         Sext Angle:         3.7.0 degrees 1st end         Hydrostatic Test Pressure:         1600.0 pounds per square inch	Round
Thread Direction:         Right-hand 1st end         Inside Diameter:         0.880 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response         Outside Diameter:         1.230 inches         Minimum Inside Bending Radius:         7.380 inches         Connection Style:         Swith unt flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Thread dinternal tube 1st end         Features Provided:         Reusable end fittings         Thready Oty Per Inch (tpi):         12 1st end         Burst Test Pressure:         3020.0 pounds per square inch         Layer Composition And Location:         1 st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabrice         Miximum Operating Pressure:         30.0 pounds per square inch         Thread Size         1 staleyer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabrice         Motion Operating Pressure:         1 302 inches 1st end         Seet Angle:         1 312 inches 1st end         Hydrostatic Test Pressure:	Thread Class:
Right-hand 1st end         Inside Diameter:         0.880 inches         Tempurture Rating:         -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response         Outside Diameter:         1.230 inches         Minimum Inside Bending Radius:         7.380 inches         Connection Style:         Swith nut flate 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Facures Provided:         Reusable end fittings         200.0 pounds per square inch         Layer Composition And Location:         1.312 inches 1st end         Harred Stare         Burst Test Pressure:         3200.0 pounds per square inch         Layer Composition And Location:         1.312 inches 1st end         Pareed Size:         3200.0 pounds per square inch         Layer Composition And Location:         1.312 inches 1st end         Pareed Size:         1.312 inches 1st end         Harred Size:         1.312 inches 1st end         Soutop uponds per square inch         Intread Size:         1.312 inches 1st end	3b 1st end
Inside Diameter:         0.880 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response         Outside Diameter:         1.230 inches         Minimum Inside Bending Radius:         7.380 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Reusable end fittings         Threaded internal tube 1st end         Peatures Provided:         Reusable end fittings         121 st end         Burst Test Pressure:         300.0 pounds per square inch         Lager Composition And Location:         1312 inches 1st end         Maximum Operating Pressure:         80.0 pounds per square inch         Strates Pressure:         1312 inches 1st end         Hyres Strate 1         1312 inches 1st end         Strates Pressure:         130.0 pounds per square inch         Hyres 1st end         Strates 1st end         Hyres 1st end         Date 1st end         Datopu	Thread Direction:
380 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response         Outside Diameter:         1.230 inches         Minimun Inside Bending Radius:         7.380 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threadd internal tube 1st end         Features Provided:         Reusable end fittings         Threadd QiV Per Inch (tpi):         12 1st end         Burst Test Pressure:         3200.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabrike         Maximum Operating Pressure:         800.0 pounds per square inch         Hared Size:         1.312 Inches 1st end         Steat Angle:         3.7.0 degrees 1st end         Hydrostatic Test Pressure:         160.0 pounds per square inch         Inside Surface Condition:         Stat Angle:         3.7.0 degrees 1st end         Hydrostatic Test Pressure:         100.0 pounds per square inch	Right-hand 1st end
Tempurature Rating:         40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response         Outside Diameter:         1.230 inches         Minimum Inside Bending Radius:         7.380 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Reusable end fittings         Thready Oxy Per Inch (tpi):         12 st end         S00.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric         Maximum Operating Pressure:         800.0 pounds per square inch         Hared Size:         1.312 inches 1st end         Hydrosatic Test Pressure:         130.0 pounds per square inch         Hydrosatic Test Pressure:         130.0 pounds per square inch         Hydrosatic Test Pressure:         1312 inches 1st end         Hydrosatic Test Pressure:         14000 pounds per square inch         Hydrosatic Test Pressure:         15000.0 pounds per square inch	Inside Diameter:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response         Outside Diameter:         1.230 inches         Minimum Inside Bending Radius:         7.380 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Reusable end fittings         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         3200.0 pounds per square inch         Layer Urbraided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric         Mirmed Size:         1312 inches 1st end         Sext Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         130.0 pounds per square inch         Hydrostatic Test Pressure:         1312 inches 1st end         Hydrostatic Test Pressure:         1300.0 pounds per square inch         Hydrostatic Test Pressure:         1312 inches 1st end         Hydrostatic Test Pressure:         1300.0 pounds per square inch         Hydrostatic Test Pressure:         1400.0 pounds per squar	0.880 inches
Outside Diameter:         1.230 inches         Minimum Inside Bending Radius:         7.380 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Reusable end fittings         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         3200.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided flabric         Maximum Operating Pressure:         800.0 pounds per square inch         Thread Size:         1.312 inches 1st end         Statiage:         37.0 degrees 1st end         Hydrosettic Test Pressure:         1600.0 pounds per square inch	Tempurature Rating:
1.330 inches         Minimun Inside Bending Radius:         7.380 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Reusable end fittings         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         300.0 pounds per square inch         Harden Machines And Location:         1st layer braided textile yam and 2nd layer braided wire and outer layer rubber impregnated braided fabric         Maximum Operating Pressure:         300.0 pounds per square inch         Strates St end         Hydrostatic Test Pressure:         37.0 degrees 1st end         Hydrostatic Test Pressure:         37.0 dogrees 1st end         Hydrostatic Test Pressure:         13.12 inches 1st end         Hydrostatic Test Pressure:         13.00 pounds per square inch         Inside Surface Condition:         Smooth         Maximum Genes 1st end         Hydrostatic Test Pressure:         148.075 inches         Maximum Genes 1st end         Hydrostatic T	-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Minimu Inside Bending Radius:         7.380 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Reusable end fittings         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         3200.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric         Maximum Operating Pressure:         800.0 pounds per square inch         Thread Size         1.312 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         1600.0 pounds per square inch         Inside Surface Condition:         Snooth         Hydrostatic Test Pressure:         1600.0 pounds per square inch	Outside Diameter:
7.380 inches         Connection Style:         Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Reusable end fittings         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         3200.0 pounds per square inch         Hayer Composition And Location:         1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabrice         Maximum Operating Pressure:         800.0 pounds per square inch         Thread Size:         1.312 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         1600.0 pounds per square inch         Inside Surface Condition:         Smoth         Measuring Method And Length:         48.875 inches         Media For Which Designed:	1.230 inches
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Thready Qty Per Inch (tpi): 12 1st end Burst Test Pressure: 3200.0 pounds per square inch Layer Composition And Location: 1 st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric Maximum Operating Pressure: 800.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 1600.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 48.875 inches	Minimum Inside Bending Radius:
Swivel nut flare 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Reusable end fittings         Thready Oty Per Inch (tpi):         12 1st end         Burst Test Pressure:         30200 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided flabric         Maximum Operating Pressure:         3020 pounds per square inch         Thread Size:         1.312 inches 1st end         Berst Test Pressure:         30.0 pounds per square inch         Hydrostatic Test Pressure:         1.312 inches 1st end         Berst Angle:         1.312 inches 1st end         Hydrostatic Test Pressure:         1600.0 pounds per square inch         Hyd	7.380 inches
End Connection Design:Straight 1st endConnection Type:Ihreaded internal tube 1st endFeatures Provided:Reusable end fittingsThready Qty Pen Inch (tpi):12 1st endBurst Test Pressure:3200.0 pounds per square inchLayer Composition And Location:Hared Size:20.0 pounds per square inch13.12 inches 1st endBurst St Pressure:30.0.0 pounds per square inchHared Size:13.12 inches 1st endBeet Angle:37.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchEnderse Size:17.0 degrees 1st endBeet Angle:17.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchHister Surface Condition:SmothKeasuring Method And Length:48.875 inchesHeasuring Method And Length:48.875 inches	Connection Style:
Straight 1st end         Connection Type:         Threaded internal tube 1st end         Features Provided:         Reusable end fittings         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         3200.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric         Maximum Operating Pressure:         800.0 pounds per square inch         Thread Size:         1.312 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         1600.0 pounds per square inch         Inside Surface Condition:         Snoth         Maximum Querting Pressure:         800.0 pounds per square inch         Beat Angle:         13.12 inches 1st end         Beat Angle:         14.00.0 pounds per square inch         Inside Surface Condition:         Snoth         Measuring Method And Length:         48.875 inches         Media For Which Designed:	Swivel nut flare 1st end
Connection Type:Threaded internal tube 1st endFeatures Provided:Reusable end fittingsThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:3200.0 pounds per square inchLayer Composition And Location:1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabricMaximum Operating Pressure:800.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmothKeusuring Method And Length:48.875 inchesMedia For Which Designed:	End Connection Design:
Hreaded internal tube 1st endFeatures Provided:Reusable end fittingsThready Qty Per Inch (tpi):12 1st endBurst Test Pressure:3200.0 pounds per square inchLayer Composition And Location:1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabricMaximum Operating Pressure:800.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmothMaximy Method And Length:48.875 inchesMedia For Which Designed:	Straight 1st end
Features Provided:Reusable end fittingsThready Qty Per Inch (tpi):12 1 st endBurst Test Pressure:3200.0 pounds per square inchLayer Composition And Location:1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabricMaximum Operating Pressure:800.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:1600.0 pounds per square inchHydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmothHasuring Method And Length:48.875 inchesHotie Tev Which Designed:	Connection Type:
Reusable end fittings         Thready Qty Per Inch (tpi):         12 1st end         Burst Test Pressure:         3200.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric         Maximum Operating Pressure:         800.0 pounds per square inch         Thread Size:         1.312 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         1600.0 pounds per square inch         Inside Surface Condition:         Smooth         Measuring Method And Length:         48.875 inches         Media For Which Designed:	Threaded internal tube 1st end
Thready Qty Per Inch (tpi):12 1st endBurst Test Pressure:3200.0 pounds per square inchLayer Composition And Location:1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabricMaximum Operating Pressure:800.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:48.875 inchesMedia For Which Designed:	Features Provided:
12 1st endBurst Test Pressure:3200.0 pounds per square inchLayer Composition And Location:1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabricMaximum Operating Pressure:800.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmoothMesuring Method And Length:48.875 inchesMedia For Which Designed:	Reusable end fittings
Burst Test Pressure:         3200.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric         Maximum Operating Pressure:         800.0 pounds per square inch         Thread Size:         1.312 inches 1st end         Seat Angle:         37.0 degrees 1st end         Hydrostatic Test Pressure:         1600.0 pounds per square inch         Inside Surface Condition:         Smooth         Measuring Method And Length:         48.875 inches         Media For Which Designed:	Thready Qty Per Inch (tpi):
3200.0 pounds per square inchLayer Composition And Location:1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabricMaximum Operating Pressure:800.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:48.875 inchesMedia For Which Designed:	12 1st end
Layer Composition And Location:1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabricMaximum Operating Pressure:800.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:48.875 inchesMedia For Which Designed:	Burst Test Pressure:
<ul> <li>1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric</li> <li>Maximum Operating Pressure:</li> <li>800.0 pounds per square inch</li> <li>Thread Size:</li> <li>1.312 inches 1st end</li> <li>Seat Angle:</li> <li>37.0 degrees 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>1600.0 pounds per square inch</li> <li>Inside Surface Condition:</li> <li>Smooth</li> <li>Measuring Method And Length:</li> <li>48.875 inches</li> <li>Media For Which Designed:</li> </ul>	3200.0 pounds per square inch
Maximum Operating Pressure:800.0 pounds per square inchThread Size:1.312 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:48.875 inchesMedia For Which Designed:	Layer Composition And Location:
800.0 pounds per square inch Thread Size: 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 1600.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 48.875 inches Media For Which Designed:	1st layer braided textile yarn and 2nd layer braided wire and outer layer rubber impregnated braided fabric
Thread Size:1.312 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:48.875 inchesMedia For Which Designed:	Maximum Operating Pressure:
<ul> <li>1.312 inches 1st end</li> <li>Seat Angle:</li> <li>37.0 degrees 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>1600.0 pounds per square inch</li> <li>Inside Surface Condition:</li> <li>Smooth</li> <li>Measuring Method And Length:</li> <li>48.875 inches</li> <li>Media For Which Designed:</li> </ul>	800.0 pounds per square inch
Seat Angle:37.0 degrees 1st endHydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:48.875 inchesMedia For Which Designed:	Thread Size:
37.0 degrees 1st end Hydrostatic Test Pressure: 1600.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 48.875 inches Media For Which Designed:	1.312 inches 1st end
Hydrostatic Test Pressure:1600.0 pounds per square inchInside Surface Condition:SmoothMeasuring Method And Length:48.875 inchesMedia For Which Designed:	Seat Angle:
1600.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 48.875 inches Media For Which Designed:	37.0 degrees 1st end
Inside Surface Condition: Smooth Measuring Method And Length: 48.875 inches Media For Which Designed:	Hydrostatic Test Pressure:
Smooth Measuring Method And Length: 48.875 inches Media For Which Designed:	1600.0 pounds per square inch
Measuring Method And Length: 48.875 inches Media For Which Designed:	Inside Surface Condition:
48.875 inches Media For Which Designed:	Smooth
Media For Which Designed:	Measuring Method And Length:
-	48.875 inches
Air and fuel/oil, hydrocarbon single response	Media For Which Designed:
	Air and fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Un 1st end

Specification Or Standard:

16 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

