Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-096-5136

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.380 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Flange Thickness:
1.500 inches 2nd end
Outside Diameter:
1.750 inches
Minimum Inside Bending Radius:
10.500 inches
Exterior Color:
Black
Flange Outside Diameter:
2.375 inches 2nd end
Connection Style:
Plain 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external tube 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fiber and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
1.500 inches 1st end
Seat Angle:
45.0 degrees 1st end
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
78.000 inches

NSN 4720-01-096-5136

Nonmetallic Hose Assembly - Page 2 of 2

Flange Style:

Round w/ out bolt holes 2nd end

## Media For Which Designed:

Fuel/oil, hydrocarbon single response

## Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A542a0

