NSN 4720-01-096-9143

15.375 inches working and 15.625 inches working

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-096-9143

Right-hand 1st end	
Inside Diameter:	
0.625 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	
Outside Diameter:	
0.850 inches	
Minimum Inside Bending Radius:	
1.500 inches	
Angle Between Rigid Elbow Fittings In Deg:	
0.0	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Elbow 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
12 1st end	
Burst Test Pressure:	
700.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided polyester cord	
Maximum Operating Pressure:	
175.0 pounds per square inch	
Thread Size:	
1.062 inches 1st end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
350.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Inside Surface Condition:	
Convoluted	
Measuring Method And Length:	

NSN 4720-01-096-9143

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

Furnished with polyethylene end closures

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0