NSN 4720-01-096-9146

Abrasion resistant and corrosion resistant

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-096-9146

Ttodila
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.998 inches
Tempurature Rating:
-54.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
1.300 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Natural
Angle Between Rigid Elbow Fittings In Deg:
90.0
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
5000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1250.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2500.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:

NSN 4720-01-096-9146

Nonmetallic Hose Assembly - Page 2 of 2



inside Surface Condition:
Convoluted
Measuring Method And Length:
18.500 inches
Thread Series Designator:
Unj 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0