NSN 4720-01-097-2833

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-097-2833

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.188 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response				
Outside Diameter:				
0.250 inches				
Minimum Inside Bending Radius:				
3.000 inches				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Reusable end fittings				
Burst Test Pressure:				
8000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided cotton cord and outer layer braided wire				
Maximum Operating Pressure:				
2000.0 pounds per square inch				
Thread Size:				
0.375 inches 1st end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
4000.0 pounds per square inch				
Flow Angle:				
45.0 degrees 2nd end				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
18.000 inches working				
Media For Which Designed:				

Air single response

NSN 4720-01-097-2833

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
1	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	D C3	igilatoi.

Unef 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0