NSN 4720-01-097-3750

Cross Sectional Shape:

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-097-3750

| Round |
|---|
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.875 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting steel comp 304 all ends |
| Fitting Component And Surface Treatment: |
| Complete fitting passivate 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Second End Relationship With First End: |
| Identical |
| Burst Test Pressure: |
| 800.0 pounds per square inch |
| First End Swivel Action Capability: |
| Not included |
| Layer Composition And Location: |
| Outer layer molded rubber, ethylene propylene err-100 |
| Maximum Operating Pressure: |
| 200.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 400.0 pounds per square inch |
| Inside Surface Condition: |

NSN 4720-01-097-3750

Nonmetallic Hose Assembly - Page 2 of 2



| Measuring Method And Le | enath: |
|-------------------------|--------|
|-------------------------|--------|

22.000 inches

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A542a0