NSN 4720-01-097-8352

Cross Sectional Shape:

Thread Direction:
Right-hand 1st end
Inside Diameter:
4.8 millimeters

Tempurature Rating:

Outside Diameter:

8.1 millimeters

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-097-8352

-297.0 degrees fahrenheit single response and 260.0 degrees fahrenheit single response

| Minimum Inside Bending Radius: | | | | | | |
|---|--|--|--|--|--|--|
| 50.8 millimeters | | | | | | |
| Exterior Color: | | | | | | |
| Natural | | | | | | |
| Connection Style: | | | | | | |
| Swivel nut with loose or integral clinch sleeve 1st end | | | | | | |
| End Connection Design: | | | | | | |
| Straight 1st end | | | | | | |
| Connection Type: | | | | | | |
| Threaded internal tube 1st end | | | | | | |
| Burst Test Pressure: | | | | | | |
| 6000.0 pounds per square inch | | | | | | |
| Layer Composition And Location: | | | | | | |
| Outer layer braided corrosion resistant steel wire | | | | | | |
| Maximum Operating Pressure: | | | | | | |
| 1500.0 pounds per square inch | | | | | | |
| Thread Size: | | | | | | |
| 10.0 millimeters 1st end | | | | | | |
| Seat Angle: | | | | | | |
| 12.0 degrees 1st end | | | | | | |
| Hydrostatic Test Pressure: | | | | | | |
| 3000.0 pounds per square inch | | | | | | |
| Inside Surface Condition: | | | | | | |
| Smooth | | | | | | |
| Measuring Method And Length: | | | | | | |
| 2250.00 millimeters working | | | | | | |
| Special Features: | | | | | | |
| With bilingual usage and direction of flow arrows labels attached | | | | | | |
| Thread Series Designator: | | | | | | |
| Iso m 1st end | | | | | | |
| Shelf Life: | | | | | | |
| N/a | | | | | | |
| | | | | | | |
| | | | | | | |

NSN 4720-01-097-8352

Nonmetallic Hose Assembly - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A542a0