## NSN 4720-01-097-8354

**Cross Sectional Shape:** 

**Thread Direction:** 

Round

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-097-8354

Right-hand 1st end
Inside Diameter:
4.8 millimeters
Tempurature Rating:
-297.0 degrees fahrenheit single response and 260.0 degrees fahrenheit single response
Outside Diameter:
8.1 millimeters
Minimum Inside Bending Radius:
50.8 millimeters
Exterior Color:
Natural
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
10.0 millimeters 2nd end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
1090.0 millimeters working
Special Features:
With bilingual usage and arrow labels
Thread Series Designator:
Iso m 2nd end
Shelf Life:

## NSN 4720-01-097-8354

Nonmetallic Hose Assembly - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A542a0