## NSN 4720-01-097-9562

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-097-9562

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.125 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Outside Diameter:
1.250 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
2500.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and outer layer braided wire
Maximum Operating Pressure:
600.0 pounds per square inch
Thread Size:
1.625 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1250.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unef 1st end

## NSN 4720-01-097-9562

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0