Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-098-9340

Cross	Sectional Shape:
Round	
Thread	Class:
3b 1st e	end
Thread	Direction:
Right-h	and 1st end
Inside	Diameter:
0.688 ir	nches
Tempu	rature Rating:
-65.0 d	egrees fahrenheit and 250.0 degrees fahrenheit single response
Outsid	e Diameter:
0.938 ir	nches
Minimu	Im Inside Bending Radius:
4.500 ir	nches
Exterio	or Color:
Natural	
Conne	ction Style:
Swivel	nut flare 1st end
End Co	onnection Design:
Straigh	t 1st end
Conne	ction Type:
Thread	ed internal tube 1st end
Feature	es Provided:
Reusat	ole end fittings
Thread	y Qty Per Inch (tpi):
12 1st e	end
Burst 1	Test Pressure:
4000.0	pounds per square inch
Layer (Composition And Location:
1st laye	er braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maxim	um Operating Pressure:
1000.0	pounds per square inch
Thread	Size:
1.062 ir	nches 1st end
Seat A	ngle:
37.0 de	grees 1st end
Hydros	static Test Pressure:
2000.0	pounds per square inch
Inside	Surface Condition:
Smooth	ı
Measu	ring Method And Length:
47 500	inches working

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 1st end

Specification Data:

81349-mil-h-83796/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-83796 spec.