Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-099-3185

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.219 inches	
Tempurature Rating:	
-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response	
Outside Diameter:	
0.469 inches	
Minimum Inside Bending Radius:	
3.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
End Fitting Component And Material:	
Complete fitting steel all ends	
Connection Type:	
Threaded internal tube 1st end	
Second End Relationship With First End:	
Identical	
Burst Test Pressure:	
24000.0 pounds per square inch	
First End Swivel Action Capability:	
Not included	
Layer Composition And Location:	
1st layer spirally laid steel wire err-100	
Unable To Decode:	
Unable to decode or unable to decode	
Maximum Operating Pressure:	
6000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
12000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	

## NSN 4720-01-099-3185

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 36.000 inches Special Features: Inner conveying tube material-plastic, polytetrafluoroethylene Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A542a0