Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-099-9454

Round Thread Class: 3) tal and Thread Direction: Right-hand 1st end Inside Diameter: 0.250 Inches Tempurature Rating: -05.0 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Connection Skyle: Swieh nut fare 1st end End Connection Design: Straight 2nd end Connection Design: Straight 2nd end Connection Type: Thread Without alue 1st end Thread View Intuk [st end] Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximu Operating Pressure: 2000.0 pounds per square inch Layer Conscition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximu Operating Pressure: 2003.0 pounds per square inch Layer Conscition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximu Operating Pressure: 2013.0 pounds per square inch Layer Conscition And Location: 37.0 degrees fat end Burst Test Pressure: 21.1 bill bill bill 22.2 bill bill 23.2 bill bill bill <td< th=""><th>Cross Sectional Shape:</th><th></th></td<>	Cross Sectional Shape:	
Bit stend Thread Direction: Right-hand 1st end Inside Diameter: -250 inches -250 inches Tempurature Rating: -250 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: -263 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: -263 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: -263 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: -263 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: -263 degrees fahrenheit and 125.0 degrees fahrenheit single response Connection Posign: Striagh 21 de end Connection Posign: Striagh 21 de end Connection Type: Thready City Pr Inch (tpl): 24 st end Bust end Polyurethane and 2nd layer spirally wrapped polyterafluoroethylene fabric and outer layer molded polyurethane Maximu Operating Pressure: 000.0 pounds per square inch Thread Strie Strie Jager st end Inside Surtace Condition: <t< th=""><th></th><th></th></t<>		
Thread Direction: Right-hand 1st end Right-hand 1st end Inside Diameter: 0.250 Inches Image: Comparison of the Compariso		
Right-hand 1st end Inside Diameter: 0.250 inches Tempurature Rating: 65.0 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Connection Style: Swive Int flare 1st end End Connection Design: Swight 2nd end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end End Connection Design: Swive Int flare st end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end End Conposition And Location: Statist Pressure: 2000.0 pounds per square inch Layer Composition And Location: Statist rest Fressure: 2000.0 pounds per square inch Layer Composition And Location: Statist end Soudon, pounds per square inch Layer Composition And Location: Statist end Soudon, pounds per square inch Layer Composition And Location: Statist end Soudon, pounds per square inch End Strike Condition: Soudon Soudon pounds per square inch Inside Strike Condition: Soudon Soudon Soudon Double per square inch Layer Condition: Soudon Thread Size 0.438 inches 1st end Soudon Base Latie Layou Condition: <tr< td=""><td></td><td></td></tr<>		
Inside Diameter: 0.250 inches Tempurature Rating: 450.0 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Design: Straight 2nd end Connection Type: Threaded infametal tube 1st end Threaded Nameal tube 1st end Sursi Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.038 inches 1st end Sursi Passes 1st end Inside Surface Condition: Smooth Messuring Method And Length: 14.000 inches Thread Seise Designator: 14.100 inches Sheft Life: Na Na	Thread Direction:	
0.250 indeks Tempurature Rating: -65.0 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Poer Ion (tpi): 24 st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 000.0 pounds per square inch Thread Size: 0.438 inches 1st end Straide Suries Condition: Straide Suries Condition: Straide Suries Condition: Straide Suries Condition: Smooth Messuring Method And Length: 14.000 inches Thread Size: 10.1 st end Layer Condition: Smooth Massuring Method And Length: 14.000 inches Thread Size Lin st end Smooth	-	
Tempurature Rating: 65.0 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end Threaded internal tube 1st end Straight 2nd end 2000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Ada sinches 1st end Straight 2nd Star Angle: 37.0 degrees 1st end Inside Surface Condition: Stardig end Maxinum Operating Pressure: 07.0 degrees 1st end Inside Surface Condition: Stardig end 14.000 inches Thread Series Designator: 14.000 inches Thread Series Designator: 14.000 inches Short Life: Na	Inside Diameter:	
-65.0 degrees fahrenheit and 125.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threadd internal tube 1st end Threadd internal tube 1st end Thready Or Per Inch (tpi): 24 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 7.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Sheft Life: Na		
Outside Diameter: 0.438 inches 0.438 inches Connection Style: Swiel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Gly Per Inch (tpi): 24 1st end Burst Test Pressure: 20000.0 pounds per square inch Eager Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 000.0 pounds per square inch Thread Safe: 0.438 inches 1st end Stat Angle: 0.438 inches 1st end Stat Angle: 0.438 inches 1st end Seat Angle: 0.438 inches 1st end Maximum Operations: 0.418 inches 1st end Strade Condition: 0.418 inches 1st end Smoth Measuring Method And Length: 14.000 inches Thread Seites Designator: Un 1st end Sheft Life: Nra Nra	Tempurature Rating:	
0.438 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready typer Inch (tpi): 24 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Besurface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Sheft Life: Na	-65.0 degrees fahrenheit and 125.0 degrees fahrenheit single response	
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Masing Method And Length: 14.000 inches Thread Series Designator: Un 1st end Sheft Life: Na Na	Outside Diameter:	
Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Sheft Life: Na	0.438 inches	
End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: Na	Connection Style:	
Straight 2nd end Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Sheft Life: N/a Un Contens: Na	Swivel nut flare 1st end	
Conection Type: Threaded internal tube 1st end Thready Qty Per Inch (tp): 24 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Sheft Life: N/a Un Cf Measure:	End Connection Design:	
Threaded internal tube 1st end Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Sheft Life: N/a Un 1st end Sheft Life:	Straight 2nd end	
Thready Qty Per Inch (tpi): 24 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a	Connection Type:	
24 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a	Threaded internal tube 1st end	
Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a	Thready Qty Per Inch (tpi):	
20000.0 pounds per square inch Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Un 5t Measure:	24 1st end	
Layer Composition And Location: 1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Sheff Life: N/a Un 1st end Sheff Life: N/a	Burst Test Pressure:	
Ist layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer molded polyurethane Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Uni Of Measure:	20000.0 pounds per square inch	
Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure:	Layer Composition And Location:	
6000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure:	1st layer molded polyurethane and 2nd layer spirally wrapped polytetrafluoroethylene fab	pric and outer layer molded polyurethane
Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure:	Maximum Operating Pressure:	
0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Uni tof Measure:	6000.0 pounds per square inch	
Seat Angle: 37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Uni Df Measure:	Thread Size:	
37.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure:	0.438 inches 1st end	
Inside Surface Condition: Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure:	Seat Angle:	
Smooth Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure:	37.0 degrees 1st end	
Measuring Method And Length: 14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure:	Inside Surface Condition:	
14.000 inches Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure:	Smooth	
Thread Series Designator: Un 1st end Shelf Life: N/a Unit Of Measure:	Measuring Method And Length:	
Un 1st end Shelf Life: N/a Unit Of Measure:	14.000 inches	
Shelf Life: N/a Unit Of Measure:	Thread Series Designator:	
N/a Unit Of Measure:	Un 1st end	
Unit Of Measure:	Shelf Life:	
	N/a	
_	Unit Of Measure:	
	No	

NSN 4720-01-099-9454

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

