

View Online at <https://aerobasegroup.com/nsn/4720-01-101-4623>

Cross Sectional Shape:

Round

Inside Diameter:

1.250 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Flange Thickness:

0.875 inches 2nd end

Outside Diameter:

2.000 inches

Minimum Inside Bending Radius:

18.000 inches

Exterior Color:

Black

Center To Center Distance Between Bolt Holes Along Width:

1.188 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.313 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.125 inches 2nd end

Flange Width:

2.391 inches 2nd end

Connection Style:

Plain 2nd end

Bolt Hole Diameter:

0.469 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Plain face flange 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided textile yarn err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

60.000 inches

Second End Swivel Action Capability:

Not included

Flange Style:

Double oval (sae split type flange) 1st end

Special Features:

Inner conveying tube material-rubber, chloroprene

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0