

View Online at <https://aerobasegroup.com/nsn/4720-01-101-5214>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

1.109 inches

Minimum Inside Bending Radius:

7.375 inches

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

1.312 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

35.000 inches

Supplementary Features:

This item has been reviewed for asbestos material; the current approved surces; 50599 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos matierla after 1984

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0