

View Online at <https://aerobasegroup.com/nsn/4720-01-101-5214>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.875 inches

**Temperature Rating:**

-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Outside Diameter:**

1.109 inches

**Minimum Inside Bending Radius:**

7.375 inches

**Connection Style:**

Swivel nut, flareless 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1250.0 pounds per square inch

**Thread Size:**

1.312 inches 2nd end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

2500.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

35.000 inches

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved surces; 50599 have indicated their part number contained asbestos prior to 1984, they continue to manufacture the same part number without asbestos matierla after 1984

**Thread Series Designator:**

Un 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0