NSN 4720-01-101-7375

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-101-7375

Cross Sectional Shape:	
Round	
Thread Class:	
3a 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.380 inches	
Tempurature Rating:	
-30.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.540 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Exterior Color:	
Black	
Connection Style:	
Inverted flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external tube 1st end	
Features Provided:	
Perforated outer cover and reusable end fittings	
Burst Test Pressure:	
5000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided polyamide cord and outer layer molded plastic	
Maximum Operating Pressure:	
1250.0 pounds per square inch	
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
2500.0 pounds per square inch	
Outer Covering Environmental Protection:	

Smooth

Measuring Method And Length:

Heat resistant and ozone resistant

Inside Surface Condition:

11.880 inches

NSN 4720-01-101-7375

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

As differentiated by o/a lg

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0