Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-101-8287

view online at https://delobasegroup.com/hsi/4720 of Tot 0207
Cross Sectional Shape:
Round
Inside Diameter:
0.500 inches
Width Across Flats:
0.563 inches 1st end
Tempurature Rating:
-65.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response
Outside Diameter:
0.921 inches
Minimum Inside Bending Radius:
5.500 inches
Quick Disconnect Size:
0.250 inches 1st end
End Application:
H-1 heater
Connection Style:
Push (internal) 1st end
End Connection Design:
Straight 1st end
Connection Type:
Internal quick disconnect 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
7000.0 pounds per square inch
Layer Composition And Location:
Outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
1000.0 pounds per square inch
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Outer Covering Environmental Protection:
Alcohol resistant and fuel resistant and hydraulic solution resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.500 inches working
Special Features:

End connections reusable, tube to hose straight adapters; tube 1/4in.Od



## Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0