

View Online at <https://aerobasegroup.com/nsn/4720-01-101-8458>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.313 inches

Temperature Rating:

-55.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.609 inches

Minimum Inside Bending Radius:

1.250 inches

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

1st layer braided fabric and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided fabric

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant and fuel resistant and vibration resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.000 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon and air and water single response

Thread Series Designator:

Unjf 1st end

Specification Data:

81349-mil-h-13444 government specification

Specification Or Standard:

3 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0