NSN 4720-01-103-8947

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-103-8947

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 90.0 degrees fahrenheit single response
Outside Diameter:
0.480 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
End Application:
J.I.Case forklift truck model m4kn
Connection Style:
Inverted flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
24 2nd end
Burst Test Pressure:
3000.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and 2nd layer braided synthetic cord and outer layer molded rubber, synthetic
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
45.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Weatherproof and ozone resistant
Inside Surface Condition:

NSN 4720-01-103-8947

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length
11.000 inches working
Media For Which Designed:
Hydraulic fluid single response
Thread Series Designator:
Uns 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A542a0