

View Online at <https://aerobasegroup.com/nsn/4720-01-104-1523>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Tempurature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit

Outside Diameter:

1.109 inches

Minimum Inside Bending Radius:

7.375 inches

First End Connection Type:

Threaded internal tube

First End Thread Class:

3b

First End Thread Direction:

Right-hand

First End Seat Angle In Deg:

37.0

First End Connection Design:

Straight

Hose Or Tubing Specification/std Data:

Mil-h-27267, size 16 specification

First End Fitting Specification/std Data:

Ms27053-16c standard

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

5000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Maximum Operating Pressure:

1250.0 pounds per square inch

First End Thread Series Designator:

Unjf

Seat Angle:

37.0 degrees 1st end

First End Thread Size:

1.312 inches

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0

Mil-std (military Standard):

Mil-h-27267 spec.