Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-104-2091

Cross Sectional Shape:
Round
Thread Class:

2b 1st end

## **Thread Direction:**

Right-hand 1st end

## **Inside Diameter:**

0.375 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

### **Outside Diameter:**

0.610 inches

Minimum Inside Bending Radius:

#### 3.000 inches

**Exterior Color:** 

Black

### **Connection Style:**

Swivel nut flare 1st end

#### **End Connection Design:**

Straight 2nd end

## **Connection Type:**

Threaded internal tube 1st end

#### Features Provided:

Nonskive

#### **Burst Test Pressure:**

1000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided fabric and outer layer molded rubber, synthetic

### Maximum Operating Pressure:

250.0 pounds per square inch

#### Thread Size:

0.562 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

#### Hydrostatic Test Pressure:

500.0 pounds per square inch

# Inside Surface Condition:

Smooth

## Measuring Method And Length:

34.125 inches

#### Media For Which Designed:

Fuel/oil, hydrocarbon and water single response

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0