NSN 4720-01-105-4069

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-105-4069 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 2.250 inches **Minimum Inside Bending Radius:** 40.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 1.875 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 2500.0 pounds per square inch **Outer Covering Environmental Protection:** Mildew resistant and ozone resistant **Inside Surface Condition:**

Smooth

Measuring Method And Length:

23.000 inches

Thread Series Designator:

Un 2nd end

NSN 4720-01-105-4069

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0