NSN 4720-01-106-5383

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-106-5383

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.438 inches
Tempurature Rating:
156.0 degrees fahrenheit single response
Outside Diameter:
0.859 inches
Minimum Inside Bending Radius:
5.750 inches
Connection Style:
Swivel nut with loose or integral clinch sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber,
chloroprene Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
-
12.0 degrees 1st end
Hydrostatic Test Pressure: 7000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and hydraulic solution resistant Inside Surface Condition:
Smooth
Measuring Method And Length: 18.600 inches working
•
Media For Which Designed: Euel/oil hydrocarbon single response
Fuel/oil, hydrocarbon single response Thread Series Designator:
Unf 1st end

96906-ms28762-8-0186 government standard

Specification Data:

NSN 4720-01-106-5383

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0