Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-107-2901

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
4.8 millimeters
Tempurature Rating:
-297.0 degrees fahrenheit single response and 260.0 degrees fahrenheit single response
Outside Diameter:
8.1 millimeters
Minimum Inside Bending Radius:
50.8 millimeters
Exterior Color:
Natural
Connection Style:
Swivel nut with loose or integral clinch sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
10.0 millimeters 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
445.00 millimeters working
Special Features:
With bilingual usage and direction of flow arrows labels on hose
Thread Series Designator:
Iso m 1st end
Shelf Life:
N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0