

View Online at <https://aerobasegroup.com/nsn/4720-01-109-7621>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-67.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.656 inches and 0.718 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-13531, type 2 or 3, class a or b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting zinc 1st end

**Connection Type:**

Threaded internal tube 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

20000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, chloroprene err-100 or 1st layer braided corrosion resistant steel wire err-100

**Maximum Operating Pressure:**

5000.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

10000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

19.000 inches working

**Thread Series Designator:**

Unf 1st end

**Specification Data:**

96906-ms500083 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-h-13531 spec.