Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-110-4392

Cross Sectional Sha	ape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.312 inches	
Tempurature Rating	j:
-65.0 degrees fahren	heit single response and 450.0 degrees fahrenheit single response
Outside Diameter:	
0.469 inches	
Minimum Inside Be	nding Radius:
4.000 inches	
Connection Style:	
Swivel nut flare 1st e	nd
End Connection De	sign:
Straight 1st end	
Connection Type:	
Threaded internal tub	be 1st end
Burst Test Pressure	
9000.0 pounds per se	quare inch
Layer Composition	And Location:
Outer layer braided of	orrosion resistant steel wire
Maximum Operating	y Pressure:
1500.0 pounds per se	quare inch
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	I
Hydrostatic Test Pr	essure:
3000.0 pounds per se	quare inch
Outer Covering Env	ironmental Protection:
Acid resistant and alo	cohol resistant and fuel resistant and oxidation resistant and solvent resistant
Vacuum In Torr:	
50.8	
Inside Surface Con	dition:
Smooth	
Measuring Method	And Length:
35.000 inches	
Thread Series Desig	gnator:
Unjf 1st end	

NSN 4720-01-110-4392

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0