NSN 4720-01-112-0915

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-112-0915

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 2a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.555 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Inverted flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external tube 1st end |
| Thready Qty Per Inch (tpi): |
| 24 1st end |
| Burst Test Pressure: |
| 6000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided rayon cord and 2nd layer braided rayon cord and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Weatherproof |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |

21.000 inches

NSN 4720-01-112-0915

Nonmetallic Hose Assembly - Page 2 of 2



| Media For Which Designe | Which Designe | ed |
|-------------------------|---------------|----|
|-------------------------|---------------|----|

Hydraulic fluid single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0